

ELECTRONIC TUBE REFERENCE

ZM3352

Specialized - Traveling Wave electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TRAVELINGWAVE

Low-noise 1.7-2.4 GHz traveling-wave amplifier with periodic-permanent-magnet focusing, 35 dB minimum gain, and 9 dB maximum noise figure.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1	TravelingWave
No fixed ratings recorded. Traveling-wave interaction structure represented as Other; published microwave performance is stored as section parameters.	

Low-noise P/L-band periodic-permanent-magnet traveling-wave amplifier with 35 dB minimum small-signal gain.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1950 General Electric Transmitting Types

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1950 GENERAL ELECTRIC TRANSMITTING TYPES

Section 1 · Traveling Wave

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Frequency Minimum	1.7 GHz	—
Frequency Maximum	2.4 GHz	—
Noise Figure Maximum	9 dB	—
Small Signal Gain Minimum	35 dB	—
Focusing Method	Periodic Permanent Magnet	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Saturation Power Output Minimum	10 mW	—